



# OASIS Premium Wood Fiber Mulch™

*Where Your Environment & Your Budget Agree!!*

**Ensure your project is to specification.  
Approved by top applicators for ease of application,  
Oasis Premium Wood Fiber Mulch™  
is the solution for your hydro-seeding projects.**

## TECHNICAL DATA

Oasis Premium Wood Fiber Mulch™ - Why, in the real world application, does it perform better? One of the components is 100% Virgin Wood chips that are non-toxic and free of contaminants in combination with developed premium cellulose fibers.

Application of Oasis Premium Wood Fiber Mulch™ forms a permeable union enhancing and developing the soil surface. This unique merger combination develops excellent water holding capacity to facilitate uniform coverage for turf growth.

## MIXING

Oasis Premium Wood Fiber Mulch™ is mixed at a rate of 50 lb. per bag with approximately 100 gallons of water.

Oasis Premium Wood Fiber Mulch™ can be applied separately or after adding seed and fertilizer to product mixing rate. Follow equipment manufacturer's installation instructions and recommendations.

In viewing application rates\*, strength of the blanket membrane can be increased to compete/compare to the Bonded Fiber Matrix you have been using by adding Oasis Tackifier™.

Depending on soil, apply with fan-type nozzle (50°) recommended tip angle straight down to drive material into the soil. Other applications will be achieved by allowing the slurry to rain down on the surface achieving approximately 70% - 80% coverage. You may wish to finish with cross-directional application of material to achieve smooth surface coverage.

Recommended Application Rates*		
Slope Gradient	US	Metric
Moderate	1,500 lbs. / Acre	1,700 kg / Ha
4:1 to 3:1	2,000 lbs. / Acre	2,300 kg / Ha
≤ 3:1 to ≤ 2:1	3,500 – 4,000 lbs. / Acre	3,920 – 4,480 kg / Ha

Oasis Tackifier™ can be added to ≤ 2:1 slope gradient where increased stability is required. Oasis Tackifier™ can be added as an excellent binder with extra soil stabilization along with dust and odor control.

Physical Properties	
Moisture Content	12% (+/- 5%)
Water Absorption	6 x Fiber Weight +/-
Eco Toxicity	Non-Toxic
100% Virgin Wood Chips	75% +/-
Premium Recycled Cellulose Fiber	18% +/-
Metering Accuracy Color	Premium Green
Biodegradable	100%
Application Rate	1,500-2,000 lbs. Per Acre
Bag Weight	50 lbs.
Package	4 mil Polyethylene Bag



- **Rapid Dispersion:** Fast mixing in jet-agitated and mechanically-agitated hydro-seeding equipment.
- **Easy Application:** Smooth shooting and high coverage slurry.
- **Resists Rainfall Impact:** Remains in place longer (for increased protection, add Oasis Tackifier™)
- **Accurate Coverage:** Premium Green encapsulated in **dissolvable green dye packet** provides a visual application gauge while adding a professional appearance to jobsite.
- **Superior Ingredients:** Manufactured from 100% Virgin Wood Chips mixed with Organic Polymer Tackifier improving the application while blending Premium Cellulose Fibers.
- **Environmentally Friendly:** Natural, environmentally friendly materials enhanced for superior performance in hydro-seeding equipment.
- **Biodegradable:** Oasis Premium Wood Fiber Mulch™ is 100% Biodegradable and non-toxic.

### PACKAGING AND SHIPPING

40 Each/50 Pound Bags per Pallet  
Full Truckload: 22 Pallets, 880 Bags



Certificate NO. 6250



12315 Robin Boulevard  
Houston, Texas 77045  
Phone: 713-413-1173  
Toll Free: 800-551-9956  
Fax: 713-433-2900  
www.ecosorb.com  
sales@ecosorb.com

\*The manufacturer makes no guarantee or warranty either expressed or implied and disclaims any and all legal liability for damages caused by the use of this material.